

List of Figures

2.1.	Time Elapsed After Start of Equalization	29
3.1.	Neutralization Accomplished by Mixing of Wastes	36
3.2.	Nomograph for Treatment of Acid Wastes: A Chart for Determining the Amount of Alkaline Agent Needed	39
3.3.	Submerged-Combustion Pilot Unit as Used by Remy and Lauria (1958)	41
3.4.	Acid Required to Neutralize Industrial Wastes in Sewer	42
4.1.	Effect of Equalization	46
4.2.	Top View of an Equalizing Basin, with Perforated Inlet Pipe and Over-and-Under Baffles	46
4.3.	Side View of an Equalizing Basin, with Mechanical Agitators Instead of Baffles	47
4.4.	Waste-Metering System	49
4.5.	Effect of Proportioning	50
5.1.	Effect of (A) Doubling the Floor Area and (B) Halving the Depth of a Settling Basin	55
5.2.	Effect of Overflow Rate on BOD Removal	56
5.3.	Flocculation Increases Settling Rate	56
5.4.	Effect of Turbulence on Particle Path	57
5.5.	(A) Fast and Good Settling Characteristics Typical of Heavy Suspended Solids. (B) Medium and Normal Settling Characteristics Typical of Homogeneous Mixture of Solids. (C) Slow and Poor Settling Characteristics Typical of Highly Colloidal and Finely Divided Solids	57
5.6.	Inlet Zone of a Circular Tank (A) Occupies 20–40% of Tank Area. Inlet Zone of a Rectangular Tank (B) Occupies only 10–15% of Tank Area	57
5.7.	(A) Circulator Tank. (B) Square Tank	58
5.8.	Typical Dispersion Curves for Various Tanks (see text for explanation). The Vertical Axis Shows the Ratio of the Actual Concentration of Contaminant (C) to the Concentration of Contaminant Mixed with the Entire Tank Volume (C_o); the Horizontal Axis Shows the Ratio of the Actual Time (t) that a Concentration Takes to Reach the End of the Tank to (T), the Total Detention Period (vol/rate) (Adapted from Camp 1953.)	59

5.9.	Graphical Analysis of Settling Test Results	63
5.10.	Rate of Rise of Air Bubbles in Tap Water (Calculated by Means of Stoke's Law) as a Function of Bubble Size	68
5.11.	Solubility of Air in Distilled Water at Various Temperatures	70
5.12.	Methods of Dissolved-Air Flotation. (A) Adhesion of a Gas Bubble to a Suspended Liquid or Solid Phase. (B) The Trapping of Gas Bubbles in a Floc Structure as the Gas Bubbles Rise. (C) The Absorption and Adsorption of Gas Bubbles in a Floc Structure as the Floc Structure is Formed (Adapted from Vrablik 1960)	71
5.13.	Schematic Drawing of Pressure Flotation System	71
5.14.	North Water Filter	72
5.15.	The 48-inch-Diameter Sweco Separator Shown Is Screening Lint from Wastewater at the Eastern Overall Company, in Baltimore, Maryland. The Wastewater Is Fed onto the 60-Mesh Market-Grade Screen at a Rate of 300 gpm. The Screened Wastewater is Discharged to the Sewer (Photograph Courtesy Sweco, Inc., Los Angeles, California)	73
5.16.	Cutaway View of a 7½-Foot-Diameter Microstrainer	74
6.1.	Effect of Colloidal Type on Viscosity	80
6.2.	Stable Colloid	83
6.3.	(A) Granula-Carbon Reactivation Cycle. (B) Adsorber Configuration for Granular Carbon Waste Treatment	85
7.1.	Typical Dialysis Flow Diagram	92
7.2.	The Desalination Process Using Energy Recovery and Artificial Intelligence Control	98
8.1.	The Role of Algae in Stabilization Ponds	108
8.2.	Accelerated-Oxidation Pilot-Plant Basins	109
8.3.	Schematic Diagram of Step-Aeration Treatment. Step I, High Sludge Seed (4,000 ppm); Step II, 2,000 ppm; Step III, 1,000 ppm; Step IV, 800 ppm	112
8.4.	<i>Sphaerotilus</i> -Like Organism, Sheathed and Unsheathed (×620)	114
8.5.	Round-Ended Rods in a Capsule of Slime (×620)	115
8.6.	Effect of Temperature on Average BOD Reduction of a Synthetic Protein-Glucose Waste, Using a Dispersed-growth Aeration System, After 24 Hours of Aeration and No Settling	115
8.7.	Schematic Arrangement of Contact-Stabilization Process	116
8.8.	Complete-Mixing Activated-Sludge System	117
8.9.	Changes in Nitrogen Occurring in Filter	120
8.10.	Diagram of Experimental Controlled-Filtration System	122
8.11.	Single-Stage Trickling Filter (with Recirculation)	123
8.12.	Two-Stage Series-Parallel Biofiltration Process	123
8.13.	Schematic Arrangement of Wet-Combustion-Process Units	124
8.14.	Typical Cavitator System	126
8.15.	Typical Surface Equipment for Deep-Well Waste Injection from Waste Sump Underground	127

8.16.	Typical Injection Well	128
8.17.	A Column Foam Fractionator	131
8.18.	Typical Layout of an Oxidation Ditch Treatment Plant	132
8.19.	A Comparison of Unit Disposal Costs	133
8.20.	Rotating Biological Contractor (RBC) Disc System	134
9.1.	Reduction of Volatile Matter in Raw Sludge by Digestion	153
9.2.	(A) The Coilfilter, a Patented Machine for the Vacuum Filtration of Sludge. This Particular Machine, in Use Since 1953 at the Sewage-Treatment Plant at St. Charles, Illinois, has Filtering Media Made up of Two Layers of Alloy Steel Coiled Springs, Each Spring Made Endless by Joining Its Two Ends with a Threaded Plug. These Springs Discharge the Filter Cake After Each Revolution of the Cylinder and Are Then Washed Before They Reenter the Vat for Another Cycle. The Material at the Left, Which Looks Like a Length of Corduroy, Is Actually a Layer of Sludge (adapted from Komline-Sanderson Engineering Corp.) (B) Schematic Drawing of the Coilfilter Shown in (a) (Courtesy Komline-Sanderson Engineering Corp.)	155
9.3.	Effect of Elutriation on FeCl_3 Required for Conditioning of Sludge	156
9.4.	Schematic Diagram of the Zimpro Process for Sewage-Sludge Oxidation	160
9.5.	Apparatus for the Atomized-Suspension Technique	162
9.6.	Effect of Stack Temperature on Thermal Efficiency	163
9.7.	Flow Diagram for Heat Balance for a Flash-Drying and Incineration System	164
9.8.	Centrifuge Bowl Schematic	166
9.9.	Schematic Plan of Thickener Mechanism and Section of Tank	170
10.1.	Twelve Alternatives of Industrial-Waste Treatment Systems	176
10.2.	Allocation of Fixed Charges on the Intercepting Sewers	196
10.3.	Allocation of Fixed Costs for Treatment Plant	197
10.4.	Cayadutta Creek	199
10.5.	Population Growth of Gloversville and Johnstown	200
10.6.	Laboratory BODs for Stations 5 and 6 at 20°C. Each Point Represents an Average of Seven Samples Collected from the Creek on 7 Different Days at Different Times of Day, All During a Drought Flow Period (October 8–18, 1964)	204
10.7.	Minimum Flow of Cayadutta Creek and Expected Recurrence of This Level	207
10.8.	BOD Reduction Required at Station 5, at 12.4°C and 2 ppm DO Remaining and Based on a Waste Discharge of 23,750 lb/day	214
10.9.	Special Design curve for Computing Treatment Plant Requirements at 12.4°C and 2 ppm DO at Station 5	214
10.10.	Activated-Sludge Treatment: BOD Reduction Related to BOD Loading	227
10.11.	Field Prototype of the Gloversville–Johnstown Joint Treatment Plant	229
10.12.	Line Diagram and Hydraulic Profile of the Gloversville–Johnstown Joint Waste–Water Treatment Plant	234
10.13.	General View of the Gloversville–Johnstown Joint Treatment Plant	235

11.1.	Definition of a Solid Waste	246
11.2.	Definition of a Hazardous Waste	247
11.3.	Special Provisions for Certain Hazardous Waste	248
11.4.	Regulations for Hazardous Waste Not Covered in Diagram 3	249
11.5.	Wood-Preserving Processes	263
11.6.	Mobile PCBX unit	272
11.7.	Supersorbon Solvent Recovery	274
11.8.	Thermal Decontamination Process flow Diagram	282
11.9.	Flameless Thermal Oxidizer	288
11.10.	Typical System	289
11.11.	Typical System	290
11.12.	An Installation	291
11.13.	Soil and Groundwater Detoxification System	309
11.14.	Detoxifier System	310
11.15.	Waste Management Services Listing Form	313
11.16.	Material Available/Wanted Listing Form	314
11.17.	Separation of Hazardous Wastes Using Membrane Filtration	316
11.18.	RCRA TSD Part B Permit Application	324
11.19.	U.S. EPA Office Locations	325
11.20.	EPA Process Permit Flowsheet	326
12.1	Treatment of Waste Gases	356
16.1.	Mass Flow Diagram of a Free-Standing Fertilizer Plant	381
16.2.	Clean Environment Surrounding the Plants	383
16.3.	Free-Standing Cement Plant	385
16.4.	Mass Flow Diagram of a Free-Standing Cement Plant	386
16.5.	Mass Flow Diagram of a Fertilizer-Cement Complex	386
16.6.	Production of Hydrogen by Electric Disassociation of Water	397
17.1A.	Dry and Wet Processing	408
17.1B.	Dry and Wet Processing	409
17.2A.	Cement-Fertilizer-Municipal Complex	410
17.2B.	Environmentally Balanced Fertilizer-Cement Plant Complex Phase	411
17.3.	Schematic Diagram Environmentally Balanced Phosphate-Fertilizer-Cement Industrial Complex	413
17.4A.	Three-Industry Complex: Tannery-Slaughterhouse-Rendering	415
17.4B.	Three-Industry Complex: Tannery-Slaughterhouse-Rendering	416
17.5.	Raw Sugar Manufacturer-Flow Diagram	419
17.6.	Sugarcane Refinery-Based EBIC (Sugarcane-Power-Alcohol Complex)	420
17.7.	Sugarcane Production	422
17.8.	Current Sugar-Mill Situation	424
17.9.	Environmentally Balanced Sugarcane Complex	428
17.10.	Diagram of the Integrated Five-Plant Industrial Complex	431
17.11.	Pulp and Paper Mill Complex	435
17.12.	Paper Mill Complex	439
18.1.	Wood-Paper Mill Complex	445

18.2.	Steel Mill–Coke and Gas Plant Complex	447
18.3.	Metal Parts–Plastic Plant Complex	448
18.4.	Metal Finishing–Plastic Manufacturing Complex	449
18.5.	Organic Chemical–Wood Preserving Plants Complex	450
18.6.	Organic Chemical–Wood Preserving Plants Complex	451
18.7.	Biomass Power Plant–Municipal–Forestry–Agriculture Complex	452
18.8.	Steel Mill–Fertilizer–Cement Complex	454
18.9.	Schematic Diagram of a Typical Rotary Steam Kiln Boiler	457
18.10A.	Schematic Flow Diagram of the EBIC for Power Plant Industry	458
18.10B.	Simple Coal Power Plant Complexes	460
18.11.	Flowchart for Polystyrene Production	463
18.12.	Tubular Reactor Process for Low-Density Polyethylene Production	464
18.13.	Philips Process for High-Density Polyethylene Production	465
18.14.	Plastic Manufacturing Industrial Complex	467
18.15.	Fluosolids System (Dorr-Oliver, Inc.)	468
18.16.	Cement, Power, and Lime Flowchart	469
18.17.	Lumber Mill Complex—Four Products	471
18.18.	Power Plant–Agriculture Complex	472
18.19.	Cannery–Agriculture Complex	474
18.20.	Nuclear Power–Glass Block Complex	475
18.21.	Feedlot–Food Production Complex	478
18.22.	Gas-Producing Plants	480
18.23.	Flow Chart of Dilute Alcohol Production	481
18.24.	Water, Electricity, Chlorine, and Lye Plants Complex	483
18.25.	Power–Aluminium–Red Brick Plants Complex	484
18.26.	Corn Food–Alcohol Production Complex	486
18.27.	Restaurant–Paint Manufacturing Complex	488
18.28.	Oil Drilling Offshore–Seashore Recreation Complex	490
18.29.	Metal Plant–Dry Cleaning–Coffee Plant Complex	491
18.30.	Electrical Storing/Converting Voltage–Wax Plant Complex	493
18.31.	Nuclear Power–Waste Recovery–Cannery Complex	495
18.32.	Coal Power Plant–Desalination Water Plant Complex	497
18.33.	Vegetable Pickling Cannery–Inorganic Chemical Complex	498
18.34.	Sugar–Ethanol–Gasoline Complex	500
18.35.	Reclaimed Wireless Phones–Cement Plant–Concrete Products Plant	502
18.36.	Sugarcane–Fuel Briquette Complex	504
18.37.	Hog Production–Animal Feed Energy–Environmental Complex	505
18.38.	Seawater Desalination Plant–Borax Plant Complex	506
18.39.	Cow Feed lot–Power Plant–Fertilizer Complex	507
18.40.	Reused Plastic Waste–Consumer Products Complex	508
18.41.	Lumbar–Textile–Cornrowing–Alcohol Producing Industrial Complex	510
19.1.	Schematic Diagram of One Type of Municipal–Industrial Complex	516
19.2.	Municipal Waste Water–Agriculture (Food) Complex	517
19.3A.	Lake Industry–Village Complex	519

19.3B.	Food-Electricity and Water Production Plant	521
20.1	The Industrial Ecosystem at Kalundborg, Denmark	528
21.1.	Unit Price Calculation	536
21.2.	Sales Values, Treatment Costs, and Sales Indices of the Pulp and Paper Industry	541